


FLEXIBLE ALUMINIUM 110 DEGREES



AUSTRALIA PACIFIC ELECTRIC CABLES

**AL Class 5 / X-HF-110 /
HFS-110-TP 0.6/1KV to AS/NZS 1125**



Conductor: Aluminium to AS/NZS 1125
Insulation: X-HF-110
Sheath: Weatherability HFS-110-TP to AS/NZS 3808

Standard Colours

Insulation: White
 Sheath: Black

Nominal conductor area mm ²	Average insulation thickness mm	Average sheath thickness mm	Approximate overall diameter mm ±10%	Approximate Mass Kg/100m ±10%	Product Code
16	0.7	1.4	10.00	12.7	FXV016A01HFS110
25	0.9	1.4	11.60	17.6	FXV025A01HFS110
35	0.9	1.4	13.40	22.3	FXV035A01HFS110
50	1.0	1.4	14.80	28.5	FXV050A01HFS110
70	1.1	1.5	17.00	37.6	FXV070A01HFS110
95	1.1	1.5	18.90	46.6	FXV095A01HFS110
120	1.2	1.6	21.10	57.8	FXV120A01HFS110
150	1.4	1.7	24.00	72.4	FXV150A01HFS110
185	1.6	1.8	25.90	87.3	FXV185A01HFS110
240	1.7	1.8	29.00	108.3	FXV240A01HFS110
300	1.8	1.9	32.00	131.9	FXV300A01HFS110
400	2.0	2.2	36.70	173.9	FXV400A01HFS110
500	2.2	2.3	40.60	213.2	FXV500A01HFS110
630	2.4	2.4	45.30	263.3	FXV630A01HFS110

Brisbane Office and Factory

89 Platinum Street,
 Crestmead, Qld 4132
 P: 07 3802 3651
 E: bnesales@apeccables.com.au

Melbourne Sales & Distribution

188 Holt Parade,
 Thomastown, VIC 3074
 P: 03 9465 1188
 E: salesmdc@apeccables.com.au

Perth Sales & Distribution

638 Casella Place
 Kewdale, WA 6105
 P: 08 9350 1300
 E: salespdc@apeccables.com.au