

FLEXIBLE SINGLE CORE TINNED COPPER



AUSTRALIA PACIFIC ELECTRIC CABLES

Applications: Wiring of Communication, Electronic Equipment and Switchboards



Conductor: Tinned Copper Wire to AS/NZS 1125
Insulation: RoHS Compliant V90HT (105) PVC to AS/NZS 3808
Sheath Colours: Black, Blue, Brown, Green/Yellow, Grey, Orange, Pink, Red, Violet, White, Yellow

Nominal conductor area mm ²	Average insulation thickness mm	AMP Rating	Electrical Resistance @ 20°C (ohm/km)	Nominal overall diameter mm	Approximate mass kg/100m	Product Code
Single Core						
1.0	0.8	17.0	20.0	3.0	1.7	FVK13202
1.5	0.8	21.0	13.7	3.15	2.2	FVK130025
2.5	0.9	29.0	8.2	3.95	3.5	FVK150025
4.0	1.0	38.0	5.1	4.75	5.3	FVK15603
6.0	1.0	49.0	3.2	5.30	7.5	FVK18403

Brisbane Office and Factory

89 Platinum Street,
Crestmead, Qld 4132
P: 07 3802 3651
E: bnsales@apeccables.com.au

Melbourne Sales & Distribution

188 Holt Parade,
Thomastown, VIC 3074
P: 03 9465 1188
E: salesmdc@apeccables.com.au

Perth Sales & Distribution

638 Casella Place
Kewdale, WA 6105
P: 08 9350 1300
E: salespdc@apeccables.com.au